

Welcome to your new pre-configured MERN stack server!

This AMI includes everything you need to start developing with MongoDB or MySQL, Express, React, and Node.js (MERN).

You'll also have VS Code Server for remote development and Nginx as a reverse proxy.

<u>Usage instructions:</u>

1. Launch the product via 1-click. **Please wait until** the instance passes <u>all</u> status checks and is running. You can connect using your Amazon private key and '<u>ubuntu</u>' login via your SSH client.

To update software, use: sudo apt update && sudo apt upgrade -y

Suggested Steps to Get Start!

Step 1: Enable and Configure Nginx

1. Open the Nginx configuration file:

sudo nano /etc/nginx/sites-available/mern

Find the line that says: "server_name" your-server-ip;

Replace your-server-ip with your actual Instance Public IP Address.

- 3. Save and exit (CTRL+X, then Y, then ENTER).
- 4. Restart Nginx to apply changes:

sudo systemctl restart nginx

Step 2: Choose Your Database (MongoDB or MySQL)

1. Navigate to the backend directory:

cd /opt/mern/backend

2. Edit the environment file:

nano .env

3. Choose Your Database:

- To Use <u>MongoDB</u>: USE_MONGO=true USE MYSQL=false
- o To Use MySQL:

USE_MONGO=false USE MYSQL=true

4. Set Your Own Password in .env under:

```
MYSQL_USER=root
MYSQL_PASSWORD=yourpassword
MYSQL_DATABASE=mern_db
```

5. Save and exit (CTRL+X, then Y, then ENTER).

Step 3: Understand Your MERN Directories

The project is structured as follows:

cd /opt/mern Is -la

You will see:

backend/ # Express.js Backend (API Server) frontend/ # React.js Frontend

- Backend: Contains API logic, Express routes, and database connections.
- Frontend: Contains React UI.

Step 4: Start React & Express

Start the backend and frontend using PM2:

```
pm2 start /opt/mern/backend/index.js --name backend
pm2 start "npm start" --name frontend --cwd /opt/mern/frontend
pm2 save
```

Verify that both are running:

pm2 list

Step 5: Test Your Backend

In your browser, go to:

http://your-public-ip/api

Ex: http://36.323.32/api

Expected Output: "MERN Backend Running"

If the API does not respond, check logs:

pm2 logs backend

Step 6: Access VS Code Server (Remote Code Editing)

Find your VS Code login password:

nano ~/.config/code-server/config.yaml

Restart VS Code Server if needed or if you change the password

sudo systemctl restart code-server@\$USER

• Open in browser:

http://your-public-ip:8085

Ex: http://36.323.32:8085

Use these commands to check if everything is running:

pm2 list sudo systemctl status nginx sudo systemctl status mongod sudo systemctl status mysql sudo systemctl status code-server@\$USER # Check backend & frontend status # Check Nginx # Check MongoDB # Check MySQL (if used) # Check VS Code Server

Step 8: Start Coding!

1. Navigate to the correct directory:

cd /opt/mern/frontend # Edit React files
cd /opt/mern/backend # Edit Express API files

Open VS Code Server and start coding remotely:

http://your-public-ip:8085

Additional Resources

- Learn **React.js**: https://react.dev/
- Learn **Express.js**: https://expressjs.com/
- Learn MongoDB: https://www.mongodb.com/docs/
- Learn MySQL: https://dev.mysql.com/doc/
- Learn PM2 Process Manager: https://pm2.keymetrics.io/

% Congratulations!

Your MERN Stack development server is now fully configured and ready for use.

Happy coding!

| _____

AWS Data

- Data Encryption Configuration: This solution does not encrypt data within the running instance.
- User Credentials are stored: /root/.ssh/authorized_keys & /home/ubuntu/.ssh/authorized_keys
- Monitor the health:
 - o Navigate to your Amazon EC2 console and verify that you're in the correct region.
 - o Choose Instance and select your launched instance.
 - Select the server to display your metadata page and choose the Status checks tab at the bottom of the page to review if your status checks passed or failed.

Extra Information: (Optional)

Allocate Elastic IP

To ensure that your instance **keeps its IP during restarts** that might happen, configure an Elastic IP. From the EC2 console:

- 1. Select ELASTIC IPs.
- 2. Click on the ALLOCATE ELASTIC IP ADDRESS.
- 3. Select the default (Amazon pool of IPv4 addresses) and click on ALLOCATE.
- 4. From the ACTIONS pull down, select ASSOCIATE ELASTIC IP ADDRESS.
- 5. In the box that comes up, note down the Elastic IP Address, which will be needed when you configure your DNS.
- 6. In the search box under INSTANCE, click and find your INSTANCE ID and then click ASSOCIATE.
- 7. Your instance now has an elastic IP associated with it.
- 8. For additional help: https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/elastic-ip-addresses-eip.html